



Product Data

R09149A

Trunk Piston Engine Oil Additive

Description

R09149A is an engine oil additive that, when mixed with the appropriate amount of diluting oil, may be used for the lubrication of medium speed trunk piston engines operating on heavy fuel.

Technical Data

Name	Method	Units	R09149A Typical Values
Viscosity, Kinematic @ 100°C	ASTM D445	mm ² /s	70
Viscosity, Kinematic @ 40°C	ASTM D445	mm ² /s	1650
Total Base Number, TBN	ASTM D2896	mg KOH/g	165
Flash Point, PMCC	ASTM D93	°C	168
Pour Point	ASTM D97	°C	-12

The above figures are typical of those blended with normal production tolerances and do not constitute a specification.

Care and Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Packaging and Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60C, exposed to hot sun or freezing conditions.

R09149A
10 Dec 2012
BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.bpmarine.com

