



## Product Data

### Energol HLP-HM Range

Anti-wear hydraulic oil

#### Description

The BP Energol™ HLP-HM hydraulic oil range are based upon highly refined mineral oil enhanced with a stabilised Zinc additive system.

#### Application

Energol HLP-HM has been specially formulated to provide good anti-wear and thermal stability performance using the very latest additive technology. The careful blend of additives with a high quality base stock ensures that Energol HLP-HM has excellent hydrolytic and oxidative stability while exhibiting a minimal tendency to produce sludge and deposits. In addition, Energol HLP-HM provides corrosion protection to ferrous and yellow metal components found within a hydraulic system. This range is designed for use in industrial hydraulic systems which require anti-wear protection. It is also suitable for other duties in which lubricants of high oxidation stability and lubrication performance are required, such as lightly loaded gears, variable speed units and bearings. The Energol HLP-HM range is fully compatible with elastomer materials commonly used for static and dynamic seals, such as nitrile, silicone and fluorinated (e.g. Viton) polymers. Energol HLP-HM is classified as follows: DIN 51502 classification – HLP ISO 6743/4 – Hydraulic Oils Type HM Energol HLP-HM grades meet the requirements (for appropriate viscosity grade) of: DIN 51524 Part 2 Cincinnati Lamb (Milacron) P 68-69-70 Denison (Parker Hannafin) HF-0 US Steel 126 & 127 Eaton (formerly Vickers) I-286-S & M-2950-S Bosch Rexroth RE90220

#### Advantages

- Good thermal and oxidative stability leads to longer operating life, reduction in lubricant costs and minimises deposit formation giving a cleaner system.
- Excellent anti-wear performance gives wear protection and reduces downtime from unscheduled maintenance.
- Good filterability characteristics (including in the presence of water), enables cost savings to be made from increased filter life and reduced maintenance.
- Excellent water separation and hydrolytic stability means reduced down time through prolonged lubricant life and increased equipment reliability.

#### Typical Characteristics

Name	Method	Units	HLP-HM 15	HLP-HM 22	HLP-HM 32	HLP-HM 46	HLP-HM 68	HLP-HM 100	HLP-HM 150
ISO Viscosity Grade	-	-	15	22	32	46	68	100	150
Density @ 15° C	ISO 12185 / ASTM D1298	g/ml	0.882	0.866	0.876	0.876	0.881	0.885	0.8874
Appearance	Visual	-	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright

Name	Method	Units	HLP-HM 15	HLP-HM 22	HLP-HM 32	HLP-HM 46	HLP-HM 68	HLP-HM 100	HLP-HM 150
Viscosity, Kinematic @ 40° C	ISO 3104 / ASTM D445	mm <sup>2</sup> /s	15	22	32	46	68	100	150
Viscosity, Kinematic @ 100° C	ISO 3104 / ASTM D445	mm <sup>2</sup> /s	3.2	4.21	5.44	6.82	8.77	12.01	14.76
Viscosity Index	ISO 2909 / ASTM 2270	-	-	>95	>95	>95	>95	>95	>95
Pour Point	ISO 3016 / ASTM D5985	°C	-27	-27	-27	-24	-21	-18	-18
Foam Sequence I	ISO 6247 / ASTM D892	mls	10/0	10/0	10/0	10/0	10/0	10/0	10/0
Water Separability @ 54°C	ISO 6614 / ASTM D1401	minutes	10	10	15	15	15	-	-
Flash Point, COC	ISO 2592 / ASTM D92	°C	180	205	210	215	226	226	232
Flash Point, PMCC	ISO 2719 / ASTM D93	°C	160	170	200	200	220	220	220
Air Release Value	ISO 9120 / ASTM D3427	minutes	4	4	4	8	8	12	24
FZG Fail State (A8.3/90)	ISO 14635-1 / DIN 51354	-	-	-	11	12	12	12	12
Rust Test, 24 hr, (Distilled Water)	ISO 7210 / ASTM D665A	-	Pass	Pass	Pass	Pass	Pass	Pass	Pass
Rust Test, 24 hr (Synthetic Sea Water)	ISO 7210 / ASTM D665B	-	Pass	Pass	Pass	Pass	Pass	Pass	Pass

Subject to usual manufacturing tolerances

Energol HLP-HM Range

12 May 2017

BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd Technopolis Knowledge Park PO Box. 19411, 1st Floor Mahakali Caves Road Mumbai - 400 093 India

Toll Free: 1800 222100 / 1800 2098100, 022-27839800 Email: [customercare.India@castrol.com](mailto:customercare.India@castrol.com)

[www.bp.com](http://www.bp.com)