



Product Data

Vanellus Multi 20W-50

For cleaner more reliable engines

Description

BP Vanellus Multi 20W-50 is a premium mineral heavy duty diesel engine oil formulated with CleanGuard™ Technology to keep your engine clean and reliable. It is suitable for use in high speed 4 stroke diesel engines that use a broad range of fuel qualities.

Advantages

BP Vanellus Multi 20W-50 with CleanGuard™ Technology helps keep your engine clean by reducing deposit build-up so that you get reliable engine performance.

As an engine works harder it will get hotter, and the higher temperatures will accelerate oil oxidation and deposit formation. Hard carbon deposits and lacquer formation lead to bore polishing and high oil consumption. BP Vanellus Multi 20W-50 with CleanGuard™ efficiently controls harmful deposits in the piston top groove under high temperature and high sulphur fuel conditions. Using BP Vanellus Multi 20W-50 you know your engine is up to 30% cleaner*

*compared with standard industry test limits



Typical Characteristics

Name	Method	Units	Vanellus Multi 20W-50
Density @ 15C	ASTM D4052	g/ml	0.884
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	18.4
Viscosity, CCS -15C (20W)	ASTM D5293	mPa.s (cP)	8085
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	163
Viscosity Index	ASTM D2270	None	123
Ash, Sulphated	ASTM D874	% wt	1.17
Total Base Number, TBN	ASTM D2896	mg KOH/g	7.9
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	212

Product Performance Claims

API CH-4

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Vanellus Multi 20W-50

08 Aug 2023

BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Lubricants UK Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Lubricants UK Telephone: 01793 512712, Automotive Technical Helpline: 0845 082 1719 Orders/Enquiries: 0845 6008125
www.bp.com