



Product Data

BP Visco 2000 15W-40

Cleanguard Engine Protection Technology

Description

Cleaner engines last longer and run better.

BP Visco's Cleanguard Engine Protection Technology™ keeps your engine cleaner for longer and fights all dirt, varnish, carbon and even deadly sludge in vital oil ways.

BP Visco engine oils slow the formation of dirt at its' source and wrap up dirt particles so they can not stick to sensitive engine parts.

Application

BP Visco 2000 15W-40 is suitable for use in automotive gasoline engines where the manufacturer recommends an API SP, API CF or earlier specification 15W-40 lubricant

Advantages

BP Visco 2000 15W-40 is a premium quality engine oil which provides:

- Proven engine cleanliness
- Reliable engine protection for normal driving conditions
- Reduced oil burnoff

Typical Characteristics

Name	Method	Units	BP Visco 2000 15W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.872
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.0
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	107
Viscosity Index	ASTM D2270	None	133
Viscosity, CCS -20C (15W)	ASTM D5293	mPa.s (cP)	6204
Pour Point	ASTM D97	°C	-36
Flash Point, PMCC	ASTM D93	°C	201
Ash, Sulphated	ASTM D874	% wt	0.70

Product Performance Claims

API CF/SP

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

BP Visco 2000 15W-40

01 Dec 2023

BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Lubricants UK Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Lubricants UK Telephone: 01793 512712, Automotive Technical Helpline: 0845 082 1719 Orders/Enquiries: 0845 6008125

www.bp.com