



Product Data

Visco 5000 FE 5W-30 Cleanguard Engine Protection Technology

Description

BP Visco with Cleanguard Engine Technology keeps your engine cleaner for longer.

BP Visco 5000 FE 5W-30 with Cleanguard Engine Protection Technology is a synthetic engine oil that provides excellent fuel economy and reduced emissions in modern vehicles from many manufacturers and especially suited for use in modern Fords.

Application

Visco 5000 FE 5W-30 is suitable for use in Automotive gasoline engines where the manufacturer recommends API SM, ILSAC GF-4, ACEA A1/B1, A5/B5 5W-30 lubricant.

Specially developed for Ford vehicles that require an oil that meets Ford WSS-M2C-913C, WSS-M2C-913B or WSS-M2C-913A

Advantages

BP Visco with Cleanguard Engine Technology keeps your engine cleaner for longer.

BP Visco 5000 FE 5W-30 is a premium quality synthetic engine oil that provides:

- Superior engine cleanliness
- Comprehensive engine protection
- Reduced harmful emissions
- Improved fuel consumption

Typical Characteristics

Name	Method	Units	BP Visco 5000 FE 5W-30
Density @ 15°C, Relative	ASTM D4052	g/ml	0.85
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.46
Viscosity, CCS -30°C	ASTM D5293	mPa.s (cP)	4680
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s	53.1
Viscosity Index	ASTM D2270	None	162
Pour Point	ASTM D97	°C	-45
Ash, Sulphated	ASTM D874	% wt	1.2
Flash Point, PMCC	ASTM D93	°C	209

Product Performance Claims

ACEA A1/B1, A5/B5

API SN/CF

ILSAC GF4

Meets Ford WSS-M2C913-A/ WSS-M2C913-B/ WSS-M2C913-C/ WSS-M2C913-D

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Visco 5000 FE 5W-30

15 Jul 2015

BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Lubricants UK Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0845 6008125 Technical Enquiries: 0845 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

www.bp.com/uk